CARING FOR ENVIRONMENT



rer tools that are no longer usable should not be disposed of with household waste but in an environmentally idly way. Please recycle where facilities exist. Check with your local council authority for recycling advice.

Recycling packaging reduces the need for landfill and raw materials. Reuse of recycled material decreases pollution in the environment. Please recycle packaging where facilities exist. Check with your local council authority for recycling advice.

WARRANTY

YOUR PRODUCT IS GUARANTEED FOR A MAXIMUM PERIOD OF 12 MONTHS FROM THE ORIGINAL DATE OF PURCHASE AND IS INTENDED FOR DIY (DO IT YOURSELF) USE ONLY. Warranty excludes consumable parts, (For example, bearings and O-rings, etc.)

30-DAY MONEY BACK GUARANTY

Within the first 30 days of purchase, you are allowed to return your product for a full refund.

30 DAYS TO 90 DAYS (3 MONTHS)
A defective unit will be replaced with a new one in accordance with the terms of this warranty, due to manufacturing fault.

90 DAYS TO 12 MONTHS
Up to 12 months after purchase, we will provide speedy and effective online service.

- WARNING!
 The following actions will result in the warranty becoming void.
- If the tool has been operated on a supply voltage other than that specified on the tool
 If the tool shows signs of damage or defects caused by or resulting from abuse, accidents or
- alterations.
- Failure to perform maintenance as set out within the user manual.
 If the product is disassembled or tampered with in any way
 Professional, industrial or high frequency use.

ANY QUESTIONS, PLEASE CONTACT OUR CUSTOMER SERVICE CENTER:

info@bielmeiertools.com

TO ENSURE THE QUICKEST RESPONSE POSSIBLE, PLEASE HAVE THE MODEL NUMBER AND DATE OF PURCHASE AVAILABLE SO OUR CUSTOMER SERVICE REPRESENTATIVE CAN ANSWER ANY QUESTIONS YOU MAY HAVE RELATING TO THE WARRANTY POLICY OR PROCEDURE.


> Yongkang Huore Industry Trading Co., Ltd. Email: info@bielmeiertools.com Add: Yuanzhou, Jiangnan Street, Yongkan City, Zhejiang, P. R. China 321300

Bielmeier

USER MANUAL

4V Max Lithium ion Cordless Staple Nail Gun

BCSK-4P



CUSTOMER SERVICE info@bielmeiertools.com

WHAT'S IN THE BOX













WARNING! Please carefully read this user manual before operating the staple gun.

ELECTRICAL SAFETY WARNINGS



Note: Bishmour cordies tools are interchangeable for use in the United States and Canada.

Note: The power cudes used for the power bookshotage must be protected by a SIRNA ground fault circuit interrupter or earth leakage circuit breaker. If the supply cord is damaged, it must be englaced by an electrical or a power for leaguest in carder to avoid a bitand.

Note: Double issuitation does not take the place of normal safety precautions when operating this tool. The insulation system is added to prevent against potential injury should an electrical faultier occor within the tool.

GENERAL POWER TOOL SAFETY WARNINGS



WARNING! Read all safety warnings and all instructions. Failure to follow the warnings and instructions may result in electric shock, fire and/or serious injury.

I Keep work rere clean and well El. Cluttered or dark areas invite accidents.

8 You work rere clean and well El. Cluttered or dark areas invite accidents.

8 You cot operate power fools in explictive atmosphere, such as in the presence of flammable liquids, gasss or dest. Power tools create sparks which may typile the dust or furnes.

8 Xeep children and bystandors at a safe distance while operating a power tool. Getting distracted while using the tool may be do in fully for the operator or bystanders if not exercit propose affects.

cold salezy. The plant match the coldet. Never modify the plag in any way. Do not use any adapter plags with earthedigmounded/power tools. Unmodified plags and matching will make one fract of electric behavior.

It is not be fract of electric behavior.

South of the plant of the plant of the place of the place of the place of the plant of the place of the plant of the place of the place of the plant of th

grounded.

B on of expose power tools to rain or wet conditions. Water entering a powe tool will increase the risk of electric shock.

Bo not also see to see the read of electric shock.

B on of expose power tools to rain or wet conditions, butter entering a powe tool will increase the risk of electric shock.

B on of expose power tool show we are the condition pulling or unphapping plan power tool. Keep cond exwey from head, of, when pedges or moving parts, Damaged or entangled an entangled or entangled or entangled and to the condition of the

For Century to the section of the se

- Power tool use and care

 a. In on from the power tool. We the correct power tool for your application. The correct power tool will do a better and safer job when used for its designed purpose.

 a. De not use the power tool. If the correct power tool for your application. The correct power tool will do a better and safer job when used for its designed purpose.

 b. Continues the power tool if the correct power tool and to the battery power tool that carenot be corrected with the work it is designed power tools.

 This help reduces the risk of stating the power tool accidentally.

 a Size risk power tool dought on the result of sides. Do not allowe persons unfamiliar with the power tool to operate it without first reading these instructions. Power tools are dangeacous in the hands of unfamed users.

 are fragingly marties appear tools. Chack for malinisignment or brinding of moving parts, breakage of parts and any other condition that may affect the power tools operation. If campage, have the power tool chapter before use. Many accidents are caused by poorly installation power tool.

GENERAL POWER TOOL SAFETY WARNINGS(CONT.)

Use the power tool, accessories, and tool bits, etc. By following these instructions, taking into account the working conditions and the work to be performed. Use of the power tool for operations different from those intended could create a hazardous altustion.

Service
alway your power loot serviced by a qualified repair person using only identical replacement parts. This will ensure that the power tool is properly and safely maintained.

If the supply cord is damage, it must be replaced by the manufacturer, its service agent or similarly qualified persons to prevent any potential hazard.

STAPLE GUN SAFETY WARNINGS



WARNING: This appliance is not intended for use by persons including children with reduced physical, sensory or mental capabilities, or lack of experience and knowledge, unless they have been given supervision or instruction concerning use of the appliance by a person responsible for their safety.

- Always assume that the tool contains fasteners. Carriess handling of the stapler or neiter can result in unexpected firing of fasteners and personal injury.
 Do not point the tool towards yourself or anyons nearby, Unexpected triggering will decharge the fastener causing an injury.
 Do not advantate the four almaiss the tool paped firmly apparts the workpice. If it she tool is not no contact with the workpice, the fastener may be deflocted away from your target.
 Do not advantate the four fasteners are contacted as the contact of the co

BATTERY AND CHARGER SAFETY WARNINGS



WARNING! This manual contains important safety and operating instructions for you battery

Before using the charger, read all instructions and cautionary markings on the charger, battery pack and the product using the battery pack.

- Product using the battery pack.


 **The charges in one briefed for our same on the than charging inchargeable batteries. Any other are many result in risk of the stacket book or electroscition.

 **Time battery to the free doctor in the charges and the charges are stated to the charges are stated and the charges are st

- excharge. The battery is not fully charged out of the carton, first read the safety instructions and then follow the charging notes and procedures.

 Save these instructions. Refer to them frequently and use them to educate others who may use this tool. If you loan this tool tosomeone, be sure they are familiar with these

KNOW YOUR PRODUCT



5

- 1. Main Housing
- 2. Safety Striker
- 3. Switch Trigger
- Magazine Latch 5 J ED Indicator

SPECIFICATIONS

- Micro Typ-C Charging Port
 ON/OFF Power Switch

Working Voltage: 4VDC Max Max Magazine Capacity: 50 Staples or Nails

Impact Rate: 50/min Staple Size: 1/4"-9/16" Type 50

Nail Size: 9/16"-5/8" Brad Battery: 4VDC Max, 1,500mAh, Li-ion


Charging Time: Approx. 2 hours (based on 5VDC/1A)


Product Weight: 1.60 lbs.


LOADING NAILS


This staple gun nailer only accepts 9/16"- 5/8" brad nails. Other types of nails will jam the unit.

- Hote on its conception country.
 Suppose the magazine letches on either side of the tool and pull the magazine out of the tool.
 Insert a row of neils into the opening behind the none pleas. Be sure to align them to the side.
 Note: Rows of more than 65 miles do not fill the states must be to the tool of marked with a nail marker so that the nail head is against the internal gr









OPERATION



WARNING! Always wear eye protection with side shields marked to comply with AMSI 287.1. Failure to do su could result in objects being thrown into your eyes and other possible sorious injuries.



WARNING! Do not allow familiarity with this product to make you careless. Remember that a careless fraction of a second is sufficient to inflict serious injury.



WARNING! Do not use this tool for fastening electrical cable or wire. It is not designed for electrical cables, causing electric shock or a fire hazard.

APPLICATIONS



WARNING! Always keep your fingers away from the discharging area of the tool wh driving a staple or nail. Fallure to keep fingers out of the way can result in serious personal injury.

DRIVING A STAPLE OR NAIL

- UNIVINITY A STAPLE UNIVINIE


 The Safety Striker System is a two step process where a staple or nail will only fine when the safety striker pin is pushed against the material to be far


 * Hood the handle firmly with the rose of the tool flat against the workpice at a 90° angle.


 * Press the safety striker pin down against the workpice to be fastered. The safety striker pin must be depressed before pulling the switch trigger.

 * The too will drive another staple each time but fugger is depressed as tong as the safety striker pin down against the workpice of the staple gun is ON before operating.

 **NOTE: Make sure that the power ON/OFF switch on the back of the staple gun is ON before operating.







UNPACK AND SETUP


CHARGING



CAUTON! The charger for this product should be protected by a limkage current device (rated at 30mA or less).

The charge indicator will illuminate red if the battery is low, indicating that the battery needs charging.

1. Plug the charging output and into the charging port on the staple gun.
2. Connect the Tip-1- cable to a DC power device such as power back, computer, or connect to an AC supply through an adaptor.
Note: The charge indicator will remain while charging.
3. Once fully charged, the indicator legit will illuminate green.







ASSEMBLY




sure the power switch is in the OFF position when assembling these parts.

LOADING STAPLES

T50 staples, other types of staples including paper staples, will jam the unit

- 1. Hold the tool upside down.
 2. Squeeze the magazine latches on either side of the tool and
 3. Insert a row of staples into the opening behind that nose piece.
 Note: Rows of more than 50 staples do not fit in the staple gun.
 4. Push the loaded magazine back into the unit until it clips into place.








OPERATION(CONT.)

How To Use Clamp

Place the materials that need to be bound on top of the wood use clamps to misist in spreading them out evenly, and then secure them in place with a nail gun.



MAINTENANCE



WARNING! To avoid serious personal injury, always be sure that the power switch of the tool is OFF position when servicing.



WARNING! Never use water or any liquids to clean or rinse off your product. Corrosive liquids, water, and chemicals can enter the product's electronic components and/or battery compartment and damage electronic components and/or the battery pack, which can result in a short circuit, increase risk of fire, and serious personal injury. Remove any buildup of dirt and debris by wiping the product clean with a dry cloth occasionally.



WARNING! When servicing, use only identical replacement parts. Use of any other parts can create a hazard or cause product damage.

When not in use, stagle nall gun should be stored in a dry, frost free joration, keep out of children's reach.
If the housing of the stagle nail gun requires cleaning, do not use colvents, Use of a cloth only is recommended. Never immore any part of the stagle nail gun into liquid.
Belimetre tools will be the responsible for my damgage or injuries counted by report for the stagle nail gun by an unauthocaed person or mishanding.

TROUBLESHOOTING



WARNING! Always make sure the power ON/OFF switch is in the OFF position before investigating the fault.


Jammed Staple Nall Gun

ne latches on either side of the tool and put the magazine out of the tool

Using a pair of pilots, remove any jammed steples or neils.

Note: Be careful not to bend the end of the magazine. If this occurs the unit will be inoperable.

With the magazine still open, tap the safety striker pin against a surface to dislodge any loose s





The Battery Has A Short Run Time Ensure that the battery is properly charged, it will take 4-5 charging cycles before the battery reaches optimum charge and run time.